FURRIONVISIONS

5" & 7" Monitor



Quick Start Guide

Models: FOS07TDBK / FOS05TDBK

This Quick Start Guide will help you install and use the Vision S monitor properly. For further support and to download the complete user manual please visit

https://furrion.com/pages/download-navigation.



Prepare

- 1. Ensure that all items in your package match those shown in the 'What's in the box' section on the packaging box.
- Before installation, please read and understand all the important safety-related instructions from the online user manual.
- 3. Prepare tools you may need, including a #2 Phillips head screwdriver, insulation tape, pencil and/or a 5/8" hole saw (needed only when drilling a new hole).

Install

Case 1: Mount in cab for observation


IMPORTANT: Choose a monitor location in your vehicle that does not block your view and complies with local laws for safe driving. Do not place in an area where it might interfere with driving.

1. Choose a mounting method.


When using the windshield stand: Clean the mounting area and remove the protective film from the suction cup. Then place the suction cup onto the appropriate location and push the locking arm downwards to stick securely.




When using the table stand: Place the table stand designed with four non-slip pads on a stable surface, and route the monitor power cable as shown.




2. Align the ball on the bracket with the opening on the back of the monitor and push firmly to lock into place.



3. Connect the cigarette lighter connector of the monitor power cable to a cigarette lighter socket.



 Connect the DC connector to the power socket on the monitor.




5. Rotate the monitor to adjust the visual angle as needed.

Case 2: Mount onto vehicle wall for security


IMPORTANT: Before any installation and wiring operation, remove the key from the ignition and isolate the 12V / 24V power source.

Always seek professional assistance if you are unsure about the installation and wiring operation.


 Mark a basic outline on the chosen location of the vehicle wall with the mounting bracket, and drill a 5/8" wiring hole as shown. Route the bare ends of the power cable on the mounting bracket through the wiring hole, and connect them to the nearest 12V/24V power supply in your vehicle. Ensure proper cable isolation for all bare ends (e.g., by using insulation tape).



2. Fix the mounting bracket onto the marked location using two flat self-tapping screws provided.




 Align the ball on the bracket with the opening on the back of the monitor and push firmly to lock into place. Ensure the metal pins on the bracket are in sound contact with those on the back of the monitor.




Pair with a camera

If this monitor comes in a bundle with one or more Furrion Vision S cameras, it is paired with the camera(s) by default. If you cannot find the video from the camera on the monitor screen or you have an unbundled camera, follow the procedures below for pairing.


- Ensure you have turned on the monitor and camera(s)
 to be paired (see the **Installation Guide** of each camera
 or the online user manual for details about camera
 installation and wiring).
- 2. Press the **MENU** button on the right of the monitor to enter the setup menu.




Tap PAIRING and then select the camera to be paired with the monitor.




4. Press the **MONITOR PAIRING** button on the camera (sharkfin camera shown) to pair it with the monitor.



5. Repeat the steps to pair the other available cameras. Erect antennas (if available) on the camera(s) and ensure the signal strength is OK.



6. Tap to choose a view mode and then a camera for view as you like.







FURRION

Furrion Innovation Center & Institute of Technology

• 52567 Independence Ct., Elkhart, IN 46514, USA

©2007-2019 Furrion Ltd. Furrion® and the Furrion logo are trademarks licensed for use by Furrion Ltd. and registered in the U.S. and other countries.