



## WF - 8725E Power Center

### Item: Specifications:

<b>Model Number</b>	WF - 8725E
<b>Power Output</b>	400 W
<b>Input Voltage</b>	190-260 Vac / 50 Hz
<b>Output Current</b>	25 A
<b>Converter Type</b>	3 Stage Charger
<b>Voltage Output</b>	13.2 - 14.4 Vdc
<b>Absorption Mode</b>	13.6 Vdc (nominal voltage)
<b>Bulk Mode</b>	14.4 Vdc (quick charging voltage)
<b>Float Mode</b>	13.2 Vdc (trickle charge voltage)

### Installation:

<b>AC Circuits:</b>	4 (Main and 3 branch circuits)
<b>DC Circuits:</b>	4 (one battery circuit)
<b>Case Material</b>	Plastic

### Safety Features/Protections:

<b>Over Current</b>	Yes
<b>Over Temperature</b>	Yes
<b>Over Voltage</b>	Yes
<b>Reverse Polarity</b>	Yes
<b>Short Circuit</b>	Yes
<b>Cooling Fan</b>	Yes

### Shipping:

<b>Dimensions</b>	11 15/16" (W) x 7 3/16" (H) x 5 1/8"
<b>Weight</b>	5.0 lbs.

### Standards:

<b>Complies with FCC</b>	Yes
--------------------------	-----



Specifications are subject to change without notice or obligation.

website: <http://www.wfcoelectronics.com>