__WF-3510-A__ Quick Setup Guide

Introduction:

The WF-3510-A user interface panel can be used as it arrives to the factory (all load functions are enabled) without performing setup; however, if the OEM desires to disable any load functions which are not present in the RV (because they are not installed in that particular floor plan), then it is required to perform setup mode.

Setup Mode:

Description: Setup Mode is used for disabling (or re-enabling) the control or display of an item on the control panel. For example: If there was only 1 awning installed on the trailer, the control for awning 2 could be disabled; or if there were only 3 holding tanks installed, the display for the remaining tank levels could be disabled.

Procedure: (Please verify power is applied to the system before performing this procedure)

1	Enter setup mode	Press and hold the SELECT Button until all display lights flash (~ 7 seconds)	SELECT > 7 seconds
2	Select an item	Quick press & release the SELECT Button to cycle through the items on the display. (Whichever item is back-lit indicates which item is selected)	SELECT
3	Enable or Disable the item	Once the item is selected, quick press & release: EXTEND Button to enable that item. RETRACT Button to disable that item.	EXTEND OR RETRACT
Repeat steps 2 & 3 for all desired items.			
4	Exit Setup Mode	***Saving Changes:*** Press and hold the SELECT Button until all display lights flash (~ 7 seconds)	SELECT > 7 seconds
		Without Saving Changes: Wait for the Display to sleep (~ 60 seconds)	> 60 seconds
5	Procedure Complete		